	1		2	3		4			
	1.54in2X ∅ 0.257in[6.53mm] THRU					ZONE	REV.	DESCRI	
A	1.54in [39.0mm]		ZA	5/16-18 UNC THRU				A	RELEASED FOR
В	[37.01111] 1.35in [34.3mm]	4.63ir [117.5m						3.00in [76.2mm]	
С	(4.79in ([121.7mm])			2.01in [51.1mm] INTERNAL	(3.38 ([85.7n				¢2. 58.4 VIEW PG29 CORD
	30S SE ENVIRONMENT RATING	RIES PROPERTIES IP68* (*RATING MAY CHANGE IF IN OUTSIDE OF	STALLER MILLS CABLE GLAND					MACHINING X.X X.XX X.XX X.XXX	
D .	COMPONENT	MATERIAL	FINISH						X.XXX 0.015" FOLD TO FOLD
	BODY/BASE	316 SS	BURNISHED					()-(X.X 0.045" X.XX 0.035"
	VIEWPORT		ABR2						X.XXX 0.020" ANGULAR 1.0°
	GASKET	SILICONE	NONE					THIS PRINT IS THE PRO	PERTY OF APG VISION LLC. THE INFORMATION CO AL. IT IS NOT TRANSFERABLE. ITS FURNISHED V IS THAT ITS NOT TO BE TRANSFERABLE.
	ARM/ADAPTOR HARDWARE	304 SS 316 SS - EXTERNAL, 18-8 SS - INTERNAL	NONE NONE						PERTY OF APG VISION LLC. THE INFORMATION CA LIT IS NOT TRANSFERABLE. IT IS FURNISHED IG THATI TI IS NOT TO BE TRACED, REPRODUCED UPACTURING WITHOUT WRITTEN PERMISSION FR NABLE UPON DEMAND. ANY INFRINGEMENT UPO'N N. WHETHER IN PART OR WHOLE, WILL BE PROSE POLICY OF CONTINUING DEVELOPMENT RVES THE RIGHT TO ALTER SPECIFICATI IOTICE.
	1		2	3		4			

